

TRICVALVE®

TRANSCATHETER BICAVAL VALVES SYSTEM

INDICATIONS FOR USE

TricValve® Transcatheter Bicaval Valves is a system of two self-expanding biological valves for the treatment of patients with hemodynamically relevant tricuspid insufficiency and caval reflux. The bioprosthesis are implanted percutaneously into the inferior and superior vena cava without disturbing the native tricuspid valve. It is especially intended for use in patients at extreme risk or who are inoperable for open surgical therapy.



DESCRIPTION

The TricValve® Transcatheter Bicaval Valves System is made of bovine pericardium leaflets sutured on a nitinol self-expanding stent system. The device is supplied sterile and is non-pyrogenic.

PACKAGING AND STORAGE CONDITION

The TricValve® Transcatheter Bicaval Valves System is packaged in a blister pack which is sealed in a double sealed Tyvek pouch and sterilized with ethylene oxide gas. The valve is pre-loaded inside the delivery system and covered with a protective capsule which is unsheathed for implantation. Store the TricValve® Transcatheter Bicaval Valves System in a dry area at room temperature (8°C to 25°C [46°F to 77°F]). Avoid exposing to extreme temperature fluctuations and direct contact with sunlight. Avoid freezing as it can damage the bioprosthesis.

WARNING: The outer surface of the sealed pouch is not sterile and therefore shall not come into contact with sterile field and instruments.

ORDER NUMBERS

ORDER NO	PRODUCT NAME		
CE-certified			
1101020025	TRICVALVE® TRANSCATHETER BICAVAL VALVE WITH DELIVERY SYSTEM FOR SVC 25		
1101020029	TRICVALVE® TRANSCATHETER BICAVAL VALVE WITH DELIVERY SYSTEM FOR SVC 29		
1101020031	TRICVALVE® TRANSCATHETER BICAVAL VALVE WITH DELIVERY SYSTEM FOR IVC 31		
1101020035	TRICVALVE® TRANSCATHETER BICAVAL VALVE WITH DELIVERY SYSTEM FOR IVC 35		
Non-CE	for Compassionate Use only		
1101020041	TRICVALVE® TRANSCATHETER BICAVAL VALVE WITH DELIVERY SYSTEM FOR IVC 41		

SIZES

TRICVALVE® MODEL	VALVE SIZE	PROXIMAL DIAMETER	DISTAL DIAMETER	MAXIMAL DIAMETER	LENGTH AFTER DEPLOYMENT
CE-certified					
SVC 25	25	25	20	35	67
SVC 29	29	29	20	40	70
IVC 31	31	34	38	38	66
IVC 35	35	38	47	47	66
Non-CE	for Compassionate Use only				
IVC 41	41	44	55	55	65



TECHNICAL SPECIFICATIONS

MEDICAL DEVICE	TRICVALVE® TRANSCATHETER BICAVAL VALVES SYSTEM			
AVAILABLE SIZE	Supervior vena cava: SVC 25; SVC 29 Inferior vena cava: IVC 31; IVC 35; IVC 41*			
TREATMENT RANGE	Superior Vena Cava SVC 25: 22mm <svc<31mm SVC 29: 27mm<svc<34mm< td=""><td colspan="2">Inferior Vena Cava IVC 31: 24mm<ivc<31mm 28mm<ivc<35mm="" 34mm<ivc<41mm<="" 35:="" 41*:="" ivc="" td=""></ivc<31mm></td></svc<34mm<></svc<31mm 	Inferior Vena Cava IVC 31: 24mm <ivc<31mm 28mm<ivc<35mm="" 34mm<ivc<41mm<="" 35:="" 41*:="" ivc="" td=""></ivc<31mm>		
ACCESS ROUTE	Transfemoral Vein access to Inferior Vena Cava / Right Atrium			
STENT FRAME MATERIAL	Laser cut nitinol wireframe stent			
CAVAL VALVE DESIGN	Self-Expanding shape memory alloy valve			
FRAME HEIGHT	At relaxed state: SVC 25: 67mm SVC 29: 70mm	At relaxed state: IVC 31: 66mm IVC 35: 66mm IVC 41*: 65mm		
DELIVERY SYSTEM	Dedicated TricValve® Delivery System			
VALVE DELIVERY METHOD	Pre-loaded valve in capsule delivered by unsheathing device			
BIOLOGICAL MATERIAL	Cross linked bovine pericardium with P+F proprietary dehydration and anti-calcification treatment.			
NUMBER OF LEAFLETS	3 bovine pericardium leaflets sutured on nitinol fame			
DEHYDRATION PROCESS	P+F proprietary process (Chemical dehydration)			
ANTI-CALCIFICATION PROCESS	P+F proprietary process (Lipid reduction; oxidative treatment; calcium chelating)			
REHYDRATION MEDIUM	Physiological saline solution			
PVL PROTECTION Polyester skirt sewn on nitinol frame				
DELIVERY SYSTEM LENGTH	865±5mm (usable length)			
GUIDEWIRE COMPATIBILITY 0.035in (0.89mm) x 260cm or 300cm Super/Extra Stiff Guidewire				
MRI CONDITIONAL	Yes			
STERILIZATION	Ethylene oxide sterilization			
PACKAGING CONDITION	Blister in double Tyvek pouch and cardboard box			
STORAGE CONDITION	Store between 8 to 25°C [46,4 to 77°F]. Do not freeze.			

^{*} Non-CE Device, Available for Compassionate Use only.



Legal Manufacturer:P+F Products + Features GmbH
Argelsrieder Feld 1a 82234
Wessling | Germany phone:
+49 8153 99 70 930

Corporate Office: P+F Products + Features GmbH Wigandgasse 5 1190 Vienna | Austria

$in fo @products and features.com \mid www.products and features.com$